

**Panasonic**  
ideas for life

# AC Servo Motor Drivers

## **MINAS LIQI**



### **Easy**

- Positioning instructions via pulse trains
- USB interface

### **Functional**

- Real-time auto-tuning
- Damping filter

### **Effective**

- High-speed position control

Automation from Panasonic:

It is easy and fast to set up a motion control project by combining a MINAS LIQI servo drive with an FP series PLC.

# MINAS LIQI

## AC Servo Motor Drivers

### Easy – functional – effective

- Servo drive controllers and motors
- Rated power 50W to 750W – 220VAC, single phase
- Positioning instructions via pulse trains
- Configure via USB using the software PANATERM®
- Damping filter, notch filter, and real-time auto-tuning function
- Easy yet multifunctional



Servo motor drives			
MINAS LIQI			
Power supply	220VAC Single phase	220VAC Single phase	220VAC Single phase
Rated output	50W-200W	400W	750W
	MBDJT2207	MBDJT2210	MCDJT3220
	D: 55.5 x H: 150 x W: 150		D: 65.5 x H: 150 x W: 190

MINAS SERVO MOTOR LIQI (MSMD***J1* - low inertia) 50W to 750W - 220VAC, single phase												
Motor type	Part no.	MSMD5AZJ1□		MSMD012J1□		MSMD022J1□		MSMD042J1□		MSMD082J1□		
Servo motor drive	MINAS LIQI	Part no.	MBDJT2207						MBDJT2210		MCDJT3220	
	Frame	Type	B								C	
Rated output	W	50		100		200		400		750		
Nominal torque (max.)	N m	0.16 (0.48)		0.32 (0.95)		0.64 (1.91)		1.3 (3.8)		2.4 (7.1)		
Rated rotational speed (max.)	min <sup>-1</sup>	3,000 (5,000)								3,000 (4,500)		
Inertia (with brake)	x10 <sup>-4</sup> kg m <sup>2</sup>	0.025 (0.027)		0.051 (0.054)		0.14 (0.16)		0.26 (0.28)		0.87 (0.97)		
Encoder	Pulses per revolution	p/r		2,500								
	Resolution	Pulses		10,000								
Degree of protection		IP65 (excluding rotor and connecting pins)										
Weight (with holding brake)	kg	0.32 (0.53)		0.47 (0.68)		0.82 (1.3)		1.2 (1.7)		2.3 (3.1)		
Motor with holding brake	with/without	without	with	without	with	without	with	without	with	without	with	
Overall length excluding shaft	mm	72	102	92	122	79.5	116	99	135.5	112.2	149.2	
Shaft length	mm	25				30				35		
Shaft diameter	mm	8 h6				11 h6		14 h6		19 h6		
Flange diameter	mm	38				60				80		

**Panasonic**®

**Panasonic Electric Works Europe AG**  
 Rudolf-Diesel-Ring 2, 83607 Holzkirchen  
 Tel. +49 (0) 8024-648-288 • Fax: +49 (0) 8024-648-111  
 info.peweu@eu.panasonic.com

[www.panasonic-electric-works.com](http://www.panasonic-electric-works.com)